



standard columns stepped steel



Holophane products that are suitable

- CityMax
- Denver Elite pole
- D-Series
- Factor
- Factor small
- V-Max



	Nominal Height	Base Diameter*	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length*	Spigot Diameter*	Shaft Diameter*	Weight kg*	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
2.5m standard duty	2500	140	1075	800	3300	400	500	100	-	-	76	27	2100
3m standard duty	3000	140	1075	800	3800	400	500	100	-	-	76	30	4666
3.5m standard duty	3500	140	1075	800	4300	400	500	100	-	-	76	32	2100
4m standard duty	4000	140	1075	800	4800	400	500	100	-	-	76	34	6484
4.5m standard duty	4500	140	1075	800	5300	400	500	100	-	-	76	37	5108
5m standard duty	5000	140	1075	800	5800	400	500	100	-	-	76	39	6149
5.5m standard duty	5500	140	1075	1000	6500	400	500	100	-	-	76	44	6003
6m standard duty	6000	140	1075	1000	7000	400	500	100	-	-	76	46	5999
6m heavy duty	5700	168	1200	1000	6700	400	600	115	130	76	89	71	10404
8m standard duty	7700	168	1200	1200	8900	400	600	115	130	76	89	89	10072
8m heavy duty	7700	168	1300	1200	9000	500	600	115	250	101	114	107	15699
8m extra heavy duty	7700	194	1300	1200	9000	500	600	115	250	127	140	136	18973
10m standard duty	9700	168	1300	1500	11200	500	600	115	250	101	114	150	18067
10m heavy duty	9700	194	1300	1500	11200	500	600	115	250	127	140	168	23193
10m extra heavy duty	9700	194	1300	1500	11200	500	600	115	250	152	168	220	28317
12m standard duty	11700	194	1300	1700	13400	500	600	115	250	127	140	213	26251
12m heavy duty	11700	194	1300	1700	13400	500	600	115	250	127	168	260	40390

* Exclusion TBC

2.5-6m std Poles	Flange Plate FB1	Bolts	M18 x 400
8-12m std Poles	Flange Plate FB2	Bolts	M24 x 820

Flange Plate and Anchor Bolt information will be confirmed at time of order due to the necessity in ensuring the correct plate and Anchor Bolts are supplied.

Column type to be confirmed at time of order as this is based on luminaire weight, windage and geographical location.

standard columns

stepped steel - CityMax Large only

post top

	Nominal Height	Base Diameter	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length	Spigot Diameter	Shaft Diameter	Weight kg	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
6m	6000	140	1075	1000	7000	400	500	115	-	-	-	46	5999
8m	7700	168	1300	1200	9000	500	600	115	100	76	114	107	15699
10m	9700	168	1300	1500	11200	500	600	115	100	76	114	150	18067
12m	11700	194	1300	1700	13400	500	600	115	100	76	140	168	26251
15m	14700	194	1200	2000	17000	400	600	115	100	76	168	306	40300

twin head

	Nominal Height	Base Diameter	Base Height	Planting Depth	Overall Length	Door to Ground	Door Opening Length	Door Opening Width	Spigot Length	Spigot Diameter	Shaft Diameter	Weight kg	Bending Moment (ULS) Nm
description	A	B	C	D	E	F	G	H	I	J	K		
8m	7400	194	1200	1200	8800	400	600	115	200	127	139.7	125	22610
10m	9400	194	1200	1500	11100	400	600	115	200	152.4	168.3	208	39131
12m	11400	194	2500	1700	13300	1000	600	115	200	152.4	168.3	295	41585

Note: For Terrain Category 2 locations LMZ, HVZ & HEZ

Anchor bolts

For columns supplied with optional flange base Holophane offers two types of foundation bolts.

Note: The material used for the bolts is Fe E500 grade steel, with yield strength 500 N/mm² and minimum UTS 550 N/mm².

- HEL.FS1 M18 Bolts (FS1) x 400 mm long
- HEL.FS2 M24 Bolts (FS2) x 820 mm long

